



Allied Bolt

Bonding Clamps



Features

- Corrosion resistant
- Silicon bronze bolt
- Clamp plated with copper, aluminum or steel wire
- UL® and CSA® Listed (C 22.2 41-M1987)
- Cast of high-strength, high copper content alloy
- Hex head bolt installs easily with commonly available linemen tools
- Parallel groove design — no need to remove bolt for installation

Application

Copper alloy split bolt connectors provide high clamping force in bonding applications.

Bonding Clamps

Ordering Information

ARRIS #	Mfg #	Description	Std Pkg
209589	2125	¼" and ⅝" Galvanized Strand to #6 Solid Copper	1 ea
036002	2125K1	1 Groove Tin Plated Copper #6 Solid - 1 Strand	1 ea
006366	2125K2	Tin Plated Copper Jumper Clamp #6 Solid - 1 Strand	1 ea

The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice. ARRIS, the ARRIS logo, Auspice®, C3™, C4®, C4c™, Cadant®, C-COR®, CHP Max®, ConvergeMedia™, Cornerstone®, CXM™, D5™, Digicon®, Flex Max®, Keystone™, MONARCH®, n5™, nABLE™, nVision®, OpsLogic®, OpsLogic® Service Visibility Portal™, PLEXIS®, PowerSense™, Regal®, ServAssure™, Service Visibility Portal™, TeleWire Supply®, TLX®, Touchstone®, VoiceAssure™, VSM™, and WorkAssure™ are all trademarks of ARRIS Group, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. © Copyright 2009 ARRIS Group, Inc. All rights reserved. Reproduction in any manner whatsoever without the express written permission of ARRIS Group, Inc. is strictly forbidden. For more information, contact ARRIS.

