



## EGT HEMI™ Head End Micro

### Specifications

---

#### VIDEO

Input	Composite Analog (NTSC)
# of Channels	1-9 channels
Encoding	MPEG-2 MP@ML
Chroma Format	4:2:0
Selectable Resolution	704, 544, 528, 352 x 480
Frame Rates	30 fps (@ full D1)
Encoded Bit Rates	2.5 – 8 Mbps
Bit Rate Modes	CBR, QBA support
Closed Captioning	SCTE – 20 (DVS157) SCTE – 21 (DVS053)
Process	Frame type and GOP adjustments
Input/Output Impedance	75Ω
Connector Type	BNC

---

#### AUDIO

Input	Analog (Unbalanced)
Operating Modes	Mono or Stereo
Encoding	MPEG-1 Layer II, Dolby Digital (AC-3)
Analog Sample Rates	32 kHz, 44.1 kHz, 48 kHz
Coding Rate	192 kHz
Input Impedance	10k Ω unbalanced
Connector Type	Mini-Stereo jack to RCA plugs

---

#### ENVIRONMENTAL

Operating Temperature Range	0°C to 50°C
Humidity	0-95%; non condensing
Power Supply Input	Volts: 115Vac Frequency: 60 Hz Amperes: 2.5 Amps
Form Factor	3RU
Dimensions	19" x 5.5" x 20.8" (WxHxD) Front Panel Lockable Doors
Capacity	Supports up to 8 video services into a single QAM channel

---

## Technical Specification

# EGT HEMI™ Head End Micro Technical Specification

---

## Specifications Continued

---

### RF INPUT

Frequency Range	50-860 MHz
Frequency bandwidth	6 MHz
Carrier Frequency Step Size	25 kHz step sizes
Channel Maps	Standard, HRC, IRC
RF Tuner Input Level	-5 to +15 dBmV
RF Bypass Input Level	+15 to +35 dBmV
Output Impedance	75 Ω
Connector Type	F-connector

---

### RF OUTPUT

Frequency Range	50-860 MHz
Frequency bandwidth	6 MHz
Carrier Frequency Step Size	25 kHz step sizes
Channel Maps	Standard, HRC, IRC
RF QAM Input Level	45 to 55 dBmV
Output Level Step Size	1 dB
RF Bypass Output Level	+10 to +35 dBmV
Output Impedance	75 Ω
Connector Type	F-connector

---

### MODULATION OUTPUT

Modulation Modes	64 QAM; 256 QAM
Symbol Rate	Up to 7 Msymbols/sec; variable
FEC	ITU-T J83 FEC annex B
Baseband Format	MPEG-2 MPTS

---

### CONFIGURATION

User Interface	Front Panel; LCD Menu Screens GUI; SNMP
----------------	---

---

Contact Customer Care for sales and product information via the ARRIS website ([www.arris.com](http://www.arris.com)) or as indicated below:

United States: 866-36-ARRIS

International: +1-678-473-5656

---

Specifications are subject to change without notice.

The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice. ARRIS, the ARRIS logo, Auspice®, C3™, C4®, C4c™, Cadant®, C-COR®, CHP Max®, ConvergeMedia™, Cornerstone®, CXM™, D5™, Digicon®, Flex Max®, Keystone™, MONARCH®, n5™, nABLE™, NSM™, nVision®, OpsLogic®, OpsLogic Service Visibility Portal™, PLEXIS®, PowerSense™, Regal®, ServAssure™, Service Visibility Portal™, TeleWire Supply®, TLX®, Touchstone®, VoiceAssure™, VSM™, and WorkAssure™ are all trademarks of ARRIS Group, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. © Copyright 2009 ARRIS Group, Inc. All rights reserved. Reproduction in any manner whatsoever without the express written permission of ARRIS Group, Inc. is strictly forbidden. For more information, contact ARRIS.



[www.arris.com](http://www.arris.com)