



# CORWave™ II / CORWave / CWDM Optical Power Meter Technical Specifications

## Specifications

Description	Model CW-PM-V1	Model CW-PM-V2	Model C2-PM-V1
Wavelength Range	1260 to 1620 nm	1260 to 1620 nm	1520 to 1570 nm
Channel Number	4 CORWave™	4 CORWave 18 CWDM	16 CORWave II
Display Resolution	20 nm (CWDM) CORWave	20 nm (CWDM) CORWave	MW01, MW02... ..MW16 CORWave II
Measurement Range (per channel)	-30 to +15 dBm	-30 to +10 dBm	-30 to +15 dBm
Accuracy	±0.5 dB/dBm	±0.5 dB/dBm	±0.5 dB/dBm
Operating Temperature	23 to 131°F (-5 to 55°C)	23 to 131°F (-5 to 55°C)	23 to 131°F (-5 to 55°C)
Storage Temperature	14 to 158°F (-10 to 70°C)	14 to 158°F (-10 to 70°C)	14 to 158°F (-10 to 70°C)
Connector Type	FC/APC, SC/APC Universal		

## Ordering Information

Model Number	Description
CW-PM-V1	CW-PM-V1: CORWave Power Meter V1 (4 CORWave Wavelengths)
CW-PM-V2	CW-PM-V2: CORWave Power Meter V2 (4 CORWave Wavelengths, 18 CWDM Wavelengths)
C2-PM-V1	C2-PM-V1: CORWave II Power Meter V1 (16 CORWave II Wavelengths)

# Technical Specification

Specifications are subject to change without notice.

The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice. ARRIS, the ARRIS logo, Auspice®, C3™, C4®, C4c™, Cadant®, C-COR®, CHP Max5000®, ConvergeMedia™, Cornerstone®, CORWave™, CXM™, D5®, Digicon®, ENCORE®, Flex Max®, HEM®®, Keystone™, MONARCH®, MOXI®, n5®, nABLE®, nVision®, OpsLogic®, OpsLogic® Service Visibility Portal™, PLEXIS®, PowerSense™, QUARTET®, Regal®, ServAssure™, Service Visibility Portal™, TeleWire Supply®, TLX®, Touchstone®, VIPr™, VSM™, and WorkAssure™ are all trademarks of ARRIS Group, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. © Copyright 2011 ARRIS Group, Inc. All rights reserved. Reproduction in any manner whatsoever without the express written permission of ARRIS Group, Inc. is strictly forbidden. For more information, contact ARRIS.

[www.arrisi.com](http://www.arrisi.com)